

Mammoth Acoustic Insulation InZone Industries Ltd.

Final Assembly: Auckland, New Zealand

Life Expectancy: 50 Year(s)

End of Life Options: Salvageable/Reusable in its Entirety,

Recyclable (100%)

Ingredients:

Polyester Hollow Conjugate Staple Fibre: Indium Tin Oxide Coated PET; Polyester Staple Non-Siliconized Fibre: Indium Tin Oxide Coated PET; Polyester Staple Fibre: Indium Tin Oxide Coated PET; Finish Oils: 1-Hydroxyoctadecane; 2-Ethylhexyl Palmitate; Dipotassium Hydrogenphosphate; Laureth-4 Phosphate; Potassium Dihexadecyl Phosphate; Flame Retardant Agent (Phosphate): 3-Hydroxyphenylphosphinyl-Propanoic Acid

Living Building Challenge Criteria: Compliant

I-13 Red List:

■ LBC Red List Free % Disclosed: 100% at 100ppm

☐ LBC Red List Approved VOC Content: Not Applicable

Declared

I-10 Interior Performance: Exception IO8-E1: Product Air Quality

Testing In Oceania

I-14 Responsible Sourcing: Not Applicable

INZ-0002 EXP. 01 MAR 2026 Original Issue Date: 2015