



Mammoth Acoustic Insulation InZone Industries Holdings Ltd

Final Assembly: Auckland, New Zealand

Life Expectancy: 90 Year(s)

End of Life Options: Salvageable/Reusable in its Entirety, Take Back Program (Auckland, Hamilton, Tauranga and Wellington), Recyclable (100%)

Ingredients:

Polyester Hollow Conjugate Staple Fibre: Indium Tin Oxide Coated PET; **Polyester Staple Non-Siliconized Fibre:** Indium Tin Oxide Coated PET; **Polyester Staple Fibre:** Indium Tin Oxide Coated PET; **Finish Oils:** 1-Hydroxyoctadecane; 2-Ethylhexyl Palmitate; Dipotassium Hydrogenphosphate; Laureth-4 Phosphate; Potassium Dihexadecyl Phosphate; **Flame Retardant Agent (Phosphate):** 3-Hydroxyphenylphosphinyl-Propanoic Acid

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| ☒ LBC Red List Free | % Disclosed: 100% at 100ppm |
| ☐ LBC Red List Approved | VOC Content: Not Applicable |
| ☐ Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

INZ-0002
EXP. 01 MAR 2027
Original Issue Date: 2015